

Simon XT*i*

Self-contained, wireless,
security system



OVERVIEW

The next-generation Simon XT*i* enhances the longstanding reliability and performance of the Simon XT™ with the advanced technology of the Two-Way Talking Touch Screen. This self-contained security system offers exclusive image capture technology, combined with powerful security and color LCD touch screen convenience, for a cost-effective, easy-to-use solution.

Well suited for houses, apartments, and condominiums, the Simon XT*i* features a built-in touch screen to control security functions. In addition to using Simon XT*i* security features for safety and peace of mind, optional wireless devices can be added to provide control over other functions including Z-Wave® wireless lighting control devices, Z-Wave wireless thermostats for home HVAC systems and Z-Wave door lock control.

All these functions can also be controlled remotely using Web portal and mobile applications powered by Alarm.com. Any Web-enabled device (laptop, smartphone or tablet) provides access to Simon XT*i*'s functionality and even includes lifestyle-enhancing information such as the current outdoor temperature and a four-day weather forecast.

The Simon XT*i* panel comes standard with 40 wireless zones, or it can be set up with 38 wireless zones and two built-in hardwired supervised burglary zones (normally-closed loop only). The built-in radio receiver works with both crystal and SAW LearnMode™ sensors.

Global Security Systems

346 Rheem Blvd. #202

Moraga, CA 94556

(800) 675-7000

(925) 377-8411

STANDARD FEATURES

- Simple, no button interface; All interaction occurs via a 3.5-inch color LCD with graphical user interface (GUI)
- At-a-glance status of home and property
- Actionable status icons
 - Identify door/window open
 - Last motion detected
 - “My property” icon status; covers all non-window, non-interior motion changes
- Menu-based system programming and test
- 40 wireless zones — two can be hardwired (normally-closed loop only)
- Built-in PSTN 2-way voice capability (over GSM with optional module)
- Supports both crystal and SAW LearnMode sensors, repeaters
- Supports 2-way RF products (version-specific)
- Chime feature for monitoring door, window or motion activity
- 1 master access code and 8 programmable user access codes of 3 to 6 digits
- SIA or CID central station reporting formats and Voice Event Notification reporting via PSTN (native) and/or optional GSM and IP modules
- Program panel with built-in touch screen or Enterprise Downloader software v4.4 or later
- Expansion options
 - Internet-based interactivity (with third-party providers)
 - Support for on-premises remote control with optional talking touchpad accessory
 - Compatible with the Interlogix Image Sensor, providing on-screen image display

FEATURES THAT SECURE YOUR HOME AND PROTECT YOUR FAMILY

Safe

Two-way communication – microphone for emergency two-way communication with monitoring station personnel

Always secure – backup power supply keeps the system operational during power failures

Effective

Emergency fast-action keys – quickly summon Fire, Medical or Police assistance with one button

Super-loud piezo siren – provides effective alert notice throughout the home

Hear clearly – Speaker for voice audio status messages and prompts, live communications with monitoring station personnel and configurable “voice chimes”

Convenient

Easy to read – color LCD touch screen provides “At-a-Glance” status of home and property

User friendly – simple, icon-driven, touch screen user interface—No buttons!

Stay connected – control lights, thermostats, door locks and other Z-Wave® enabled devices.



At-A-Glance Home Status

Quick, at-a-glance home status provides a complete view of home systems including security, indoor temperature and weather.



Electronic Keypad

Offers user-friendly system control and operation via the electronic keypad.



Options to make the most of your system

With the optional GSM reporting and Alarm.com features, Simon XT_i enables remote monitoring and control of your security system for convenient and effective home protection.

- Receive voice, email or text message reports
- Remote lighting, locks and thermostat control
- Monitor household activity in real time
- Arm/Disarm Simon XT_i from anywhere
- Image capture and display via wireless Image Sensors
- Powered by Alarm.com for advanced interactive services
 - Optional HVAC, lighting, and lock control devices with programmable options help promote energy savings
 - Four-day weather forecast adds value and lifestyle convenience
 - Z-Wave door lock support and indicator status

Optional Service



Thermostatic Control

Thermostatic control makes it easy to set automation schedules in conjunction with lighting and security events to save energy and reduce utility bills.



Menu-Based System Programming

Menu-based system programming and testing enables fast and accurate installation of the panel and supported devices.

Specifications

Electrical

Required transformer	Class II, 9 VAC, 3.34A, 60 Hz (60-899, 60-899-CN in Canada)
Fuse	Non-replaceable transformer fuse
Backup batteries	6 VDC, 1.2 Ah lead acid (60-914)
Backup time	24 hours (fully charged)
Battery test	10 seconds under load every 4 hours

Radio receiver

Type	SAW-controlled superheterodyne
Frequency	319.5 MHz/ Bandwidth 350 kHz
Sensitivity	110 dBm nominal
Nom. range without GSM module present	1000-ft. open-air receiving range
Nom. range with GSM module present	Approx. 500-ft. open-air receiving range

Telephone/modem

Dialing	DTMF or pulse
Modem	Modified Bell 103 (110 or 300 bps)
Telephone interface	Line seizure relay

Inputs/outputs

Total input zones	40 or 38 wireless and 2 hardwire (normally-closed loop only)
Auxiliary power	Unregulated 5.1 to 12 VDC; power-limited to 250 mA (maximum) @ 10 VDC
Siren output	1 Hardwire Interior Siren (5.1 to 9 VDC)

Digitized voice

Digitization type	Continuous Variable Slope Delta (CVSD) Modulation
Playback rate	88,200 bits/second

Environmental

Operating temperature	32 to 122°F (0 to 49°C)
Relative humidity	90% max., non-condensing

Physical

Color	White
Dimensions (LxWxD)	5.81 x 7.12 x 1.60 in. (147 x 180 x 40 mm)
Weight, without battery	1.0 lb. (454 g)
Installation	Wall mount
Construction, chassis	ABS

Regulatory

FCC	Part 15, Part 68
UL	985, 1023, 1635/ULC Listing ORD-C102319-74,ULC-S545-M89
CSFM	California State Fire Marshall
CP01-2007	

Ordering Information

Simon XTi Packages

80-632-3N-XTi	Simon XTi starter package without X10
80-517-3N-XTi	Simon XTi 3/1/1 SAW package A5 without X10
80-649-3N-XTi	Simon XTi Crystal package C5 without X10
80-649-3D-XTi-GSM-TM	Simon XTi 3/1/1 Kit w/Z-Wave, GSM for T-Mobile Network
80-649-3N-XTi-TS-TM	Simon XTi w/Two-Way Talking Touch Screen & GSM Kit
80-649-3N-XTi-TS	Simon XTi w/Two-Way Talking Touch Screen

Accessories (sample list of compatible devices)

60-362N-10-319.5	Crystal door/window sensor
60-670-95R	SAW door/window sensor
600-1064-95R	4-button keychain (keyfob)
60-906-95	Wrist panic sensor
60-807-95R	SAW pet immune motion sensor
13-949	Interior siren
13-950	Exterior siren
60-924-RF-TS	Simon XT Two-Way Talking Touch Screen
TX-6310-01-1	Carbon Monoxide
TX-3030-01-1	DesignLine flat wall touchpad
TX-1010-01-1	DesignLine door/window sensor
TX-4014-01-2	DesignLine 4-button keypad
TX-6010-01-1	Smoke detector
60-744-95R	Water sensor
60-742-95R	Freeze sensor
600-1048-XT-ZX-TM	GSM radio for XT/XTi with Z-Wave and Image Sensor ready (T-Mobile)
600-1048-XT-ZX-AT	GSM radio for XT/XTi with Z-Wave and Image Sensor ready (AT&T)
600-9400-IMAG	Image Sensor
IS-ZW-TSTAT-300	Z-Wave advanced thermostat
IS-ZW-AM-1	Z-Wave plug-in fluorescent light and appliance module
IS-ZW-LM-1	Z-Wave plug-in lamp module
IS-ZW-OM-1	Z-Wave outdoor module
IS-ZW-WS-1	Z-Wave in-wall on/off switch

Synchronized Homes to keep families connected, protected and a whole lot more.

The Simon XTi is designed to support a variety of accessories that heighten security and enhance convenience. These options make it easy to customize systems that meet each user's specific need and priorities.

SECURITY



Two-Way Talking Touch Screen



Keyfob



Door/Window sensors



PIR motion detector



Glassbreak sensor



Video camera



Environmental sensor



Image sensor

LIFE SAFETY



Smoke and heat detector



Carbon Monoxide detector

LIFESTYLE



Locks



Thermostats



Appliance/Lamp modules



Lighting

INTERACTIVE SERVICES




Interactive Services

powered by  **ALARM.COM**[™]

Specifications subject to change without notice.

© 2012 Interlogix. All rights reserved.

Z-Wave® is a registered US Trademark of Zensys A/S. Complies with FCC and Industry Canada regulations.

 is a trademark of General Electric Company and is used under license to UTC Fire & Security, 9 Farm Springs Road, Farmington, CT 06034-4065

203-3508 2012/05 (69868)

Global Security Systems
346 Rheem Blvd. #202
Moraga, CA 94556
(800) 675-7000
(925) 377-8411

 **interlogix**

interlogix.com